

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Oct 2025

Print date: 13 Oct 2025

Version: 2.2

OBTEGO
innovative surface protection

Page 1/10

OBTEGO X-100 (A) Harz (Primer)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation:

OBTEGO X-100 (A) Harz (Primer)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture:

Low-viscosity primer for OBTEGO X-200 joint resin and X-300 mortar.

1.3. Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor):

OBTEGO AG

Landshuter Straße 36

84051 Essenbach/Altheim

Germany

Telephone: +49 8703/93844-0

Telefax: +49 8703/93844-29

E-mail: sdb@obtego.com

Website: www.obtego.com

E-mail (competent person): sdb@obtego.com

1.4. Emergency telephone number

24h: +49(0)89-19240

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
flammable liquids (<i>Flam. Liq. 2</i>)	H225: Highly flammable liquid and vapour.	
Skin corrosion/irritation (<i>Skin Irrit. 2</i>)	H315: Causes skin irritation.	
Respiratory or skin sensitisation (<i>Skin Sens. 1</i>)	H317: May cause an allergic skin reaction.	
STOT-single exposure (<i>STOT SE 3</i>)	H335: May cause respiratory irritation.	

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms:



GHS02
Flame



GHS07
Exclamation mark

Signal word: Danger

Hazard statements for physical hazards

H225 Highly flammable liquid and vapour.

Hazard statements for health hazards

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Oct 2025

Print date: 13 Oct 2025

Version: 2.2

OBTEGO
innovative surface protection

Page 2/10

OBTEGO X-100 (A) Harz (Primer)

Hazard statements for health hazards

H335 May cause respiratory irritation.

Supplemental hazard information

EUH208 Contains 1,4-Butandioldimethacrylat; N-Hydroxyethyl-N-methyl-p-toluidine. May produce an allergic reaction.

Precautionary statements Prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P243 Take action to prevent static discharges.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements Response

P370 + P378 In case of fire: Use Carbon dioxide (CO2) or Water spray jet to extinguish.

Precautionary statements Storage

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

Precautionary statements Disposal

P501 Dispose of contents/container to an appropriate recycling or disposal facility.




2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients / Hazardous impurities / Stabilisers:

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 80-62-6 EC No.: 201-297-1 Index No.: 607-035-00-6	methyl methacrylate Flam. Liq. 2 (H225), STOT SE 3 (H335), Skin Irrit. 2 (H315), Skin Sens. 1 (H317)  Danger	50 - ≤ 100 weight-%
CAS No.: 2082-81-7 EC No.: 218-218-1 Index No.: 607-766-00-0	tetramethylene dimethacrylate Skin Sens. 1B (H317)  Warning	0.5 - ≤ 2.5 weight-%
CAS No.: 2842-44-6 EC No.: 220-638-5	2-(N-methyl-p-toluidino)ethanol Aquatic Chronic 2 (H411), Eye Irrit. 2 (H319), Skin Sens. 1 (H317)  Warning	0.5 - ≤ 2.5 weight-%

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Remove victim out of the danger area. Remove contaminated, saturated clothing. If unconscious but breathing normally, place in recovery position and seek medical advice. Do not leave affected person unattended.

Following inhalation:

Provide fresh air. In case of respiratory tract irritation, consult a physician.

In case of skin contact:

If skin irritation or rash occurs: Get medical advice/attention. Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap.

After eye contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately. In case of contact with eyes, rinse immediately thoroughly with plenty of edible oil and consult an ophthalmologist.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Oct 2025

Print date: 13 Oct 2025

Version: 2.2

OBTEGO
innovative surface protection

Page 3/10

OBTEGO X-100 (A) Harz (Primer)

Following ingestion:

Rinse mouth. If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Get medical advice/attention if you feel unwell. Let 1 glass of water be drunk in little sips (dilution effect).

Self-protection of the first aider:

Use personal protection equipment.

4.2. Most important symptoms and effects, both acute and delayed

Skin corrosion/irritation Allergic reactions Irritation to respiratory tract

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Foam Sand CO₂, Extinguishing powder / Water spray jet
alcohol resistant foam Carbon dioxide (CO₂)

Unsuitable extinguishing media:

Full water jet

5.2. Special hazards arising from the substance or mixture

In case of fire: Hydrocarbons, Carbon monoxide & Carbon dioxide Combustible

Hazardous combustion products:

In case of fire: Gases/vapours, toxic Hydrocarbons Carbon monoxide Carbon dioxide (CO₂)

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

5.4. Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Remove persons to safety.

Protective equipment:

Wear protective gloves/protective clothing/eye protection/face protection.

Emergency procedures:

Eliminate all ignition sources if safe to do so.

6.1.2. For emergency responders

Personal protection equipment:

Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment:

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up:

Do not rinse down with water. Water (with cleaning agent)

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

6.5. Additional information

Use appropriate container to avoid environmental contamination.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Oct 2025

Print date: 13 Oct 2025

Version: 2.2

OBTEGO
innovative surface protection

Page 4/10

OBTEGO X-100 (A) Harz (Primer)

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Wear personal protection equipment (refer to section 8). If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means. Keep container tightly closed in a cool, well-ventilated place.

Fire prevent measures:

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Keep container tightly closed in a cool, well-ventilated place. Vapours can form explosive mixtures with air.

Advices on general occupational hygiene

When using do not eat, drink, smoke, sniff. Avoid contact with skin, eyes and clothes.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions:

Keep container tightly closed in a cool, well-ventilated place.

Requirements for storage rooms and vessels:

Keep container tightly closed in a cool, well-ventilated place. Keep/Store only in original container. Do not allow to enter into surface water or drains. Keep container tightly closed.

Storage class (TRGS 510, Germany): 3 - Flammable liquids

Further information on storage conditions:

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

7.3. Specific end use(s)

GISCODE:

RMA 10

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
IOELV (EU)	methyl methacrylate CAS No.: 80-62-6 EC No.: 201-297-1	① 50 ppm ② 100 ppm
TRGS 900 (DE)	methyl methacrylate CAS No.: 80-62-6 EC No.: 201-297-1	① 50 ppm (210 mg/m ³) ② 100 ppm (420 mg/m ³) ⑤ DFG, EU, Y

8.1.2. Biological limit values

No data available

8.1.3. DNEL-/PNEC-values

Substance name	DNEL value	① DNEL type ② Exposure route
methyl methacrylate CAS No.: 80-62-6 EC No.: 201-297-1	210 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects
methyl methacrylate CAS No.: 80-62-6 EC No.: 201-297-1	13.67 mg/kg bw/day	① DNEL worker ② Long-term - dermal, local effects

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Oct 2025

Print date: 13 Oct 2025

Version: 2.2

OBTEGO
innovative surface protection

Page 5/10

OBTEGO X-100 (A) Harz (Primer)

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No data available

8.2.2. Personal protection equipment



Eye/face protection:

Eye glasses with side protection EN 166

Skin protection:

Tested protective gloves must be worn EN ISO 374 Suitable material: Butyl caoutchouc (butyl rubber)
Breakthrough time: 60 min In the case of wanting to use the gloves again, clean them before taking off and air them well. Breakthrough times and swelling properties of the material must be taken into consideration.

Respiratory protection:

Suitable respiratory protection apparatus: Recommendation. Filter type: A for short-term use EN 14387

Other protection measures:

Keep away from: Food and feedingstuffs

8.2.3. Environmental exposure controls

No data available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state: Liquid

Form: Liquid

Colour: gelblich

Odour: not determined

flammability: Yes

Safety relevant basis data

Parameter	Value	at °C	① Method ② Remark
pH	No data available		
Melting point	-48 °C		
Freezing point	No data available		
Initial boiling point and boiling range	100 °C		
Flash point	10 °C		
Evaporation rate	No data available		
Auto-ignition temperature	430 °C		
Upper/lower flammability or explosive limits	2.1 - 12.5 Vol-%		
Vapour pressure	38.7 hPa	20 °C	
Vapour density	No data available		
Density	0.97 g/cm ³		
Bulk density	not applicable		
Water solubility	practically insoluble		
Dynamic viscosity	No data available		
Kinematic viscosity	No data available		

9.2. Other information

Organic solvents 0,0%

9.2.1. Information with regard to physical hazard classes

Explosives:

The product is not explosive, but the formation of explosive vapour/air mixtures is possible.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Oct 2025

Print date: 13 Oct 2025

Version: 2.2

OBTEGO
innovative surface protection

Page 6/10

OBTEGO X-100 (A) Harz (Primer)

Flammable liquids:

Highly flammable liquid and vapour.

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapour. Highly flammable liquid and vapour.

10.2. Chemical stability

Avoid high temperatures or direct sunlight.

10.3. Possibility of hazardous reactions

Can polymerise exothermically in the absence of stabilisers, particularly in acid conditions or if shelf life exceeded.

10.4. Conditions to avoid

No further relevant information available.

10.5. Incompatible materials

Reaction with: Peroxides & Radical former

10.6. Hazardous decomposition products

Hydrocarbons Carbon monoxide & Carbon dioxide Gases/vapours, toxic

Further information

Do not allow to enter into surface water or drains.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

methyl methacrylate CAS No.: 80-62-6 EC No.: 201-297-1
LD₅₀ oral: 7,870 mg/kg (Rat)
LD₅₀ dermal: >5,000 mg/kg (Rabbit)
LC₅₀ Acute inhalation toxicity (dust/mist): 29.8 mg/L 4 h (Rat)
2-(N-methyl-p-toluidino)ethanol CAS No.: 2842-44-6 EC No.: 220-638-5
LD₅₀ oral: >2,000 mg/kg (rat) EPA OPPTS 870.1100 (Acute Oral Toxicity)

Acute oral toxicity:

Based on available data, the classification criteria are not met.

Acute dermal toxicity:

Based on available data, the classification criteria are not met.

Acute inhalation toxicity:

Based on available data, the classification criteria are not met.

Skin corrosion/irritation:

Causes skin irritation.

Serious eye damage/irritation:

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation:

May cause an allergic skin reaction. Contains 2-(N-methyl-p-toluidino)ethanol. May produce an allergic reaction.

Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity:

Based on available data, the classification criteria are not met.

STOT-single exposure:

May cause respiratory irritation.

STOT-repeated exposure:

Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Oct 2025

Print date: 13 Oct 2025

Version: 2.2

OBTEGO
innovative surface protection

Page 7/10

OBTEGO X-100 (A) Harz (Primer)

Aspiration hazard:

Based on available data, the classification criteria are not met.

Additional information:

No data available

11.2. Information on other hazards

Endocrine disrupting properties:

128-37-0 2,6-Di-tert-butyl-p-kresol Liste II

SECTION 12: Ecological information

12.1. Toxicity

methyl methacrylate CAS No.: 80-62-6 EC No.: 201-297-1

LC₅₀: 311 mg/L 4 d (fish)

EC₅₀: 170 mg/L 4 d (Senastrum capricornutum)

EC₅₀: 69 mg/L 2 d (Daphnia magna (Big water flea))

NOEC: >110 mg/L 3 d (Senastrum capricornutum)

NOEC: 37 mg/L (Daphnia magna (Big water flea))

2-(N-methyl-p-toluidino)ethanol CAS No.: 2842-44-6 EC No.: 220-638-5

LC₅₀: 7.03 mg/L 2 d (crustaceans, Daphnia magna) OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

NOEC: 10 mg/L 3 d (Algae/water plant, Desmodesmus subspicatus (previous name: Scenedesmus subspicatus))
OECD Guideline 201 (Freshwater Alga and Cyanobacteria, Growth Inhibition Test)

NOEC: 4.6 mg/L 2 d (crustaceans, Daphnia magna) OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

LOEC: 32 mg/L 3 d (Algae/water plant, Desmodesmus subspicatus (previous name: Scenedesmus subspicatus))
OECD Guideline 201 (Freshwater Alga and Cyanobacteria, Growth Inhibition Test)

LOEC: 10 mg/L 2 d (crustaceans, Daphnia magna) OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

12.2. Persistence and degradability

Additional information:

Do not enter groundwater, bodies of water or sewers undiluted or in large quantities
let.

12.3. Bioaccumulative potential

2-(N-methyl-p-toluidino)ethanol CAS No.: 2842-44-6 EC No.: 220-638-5

Log K_{ow}: 2.2

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

methyl methacrylate CAS No.: 80-62-6 EC No.: 201-297-1

Results of PBT and vPvB assessment: —

2-(N-methyl-p-toluidino)ethanol CAS No.: 2842-44-6 EC No.: 220-638-5

Results of PBT and vPvB assessment: This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

12.6. Endocrine disrupting properties

Endocrine disrupting properties Section 11: Toxicological Information

Based on available data, the classification criteria are not met.

12.7. Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Dispose of waste according to applicable legislation. Do not allow to enter into surface water or drains.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Oct 2025

Print date: 13 Oct 2025

Version: 2.2

OBTEGO
innovative surface protection

Page 8/10

OBTEGO X-100 (A) Harz (Primer)

13.1.1. Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Waste code product

07 02 08 *	other still bottoms and reaction residues
------------	---

*: Evidence for disposal must be provided.

Directive 2008/98/EC (Waste Framework Directive)

HP 3	Flammable
HP 4	Irritant – skin irritation and eye damage
HP 5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP 13	Sensitising

Waste code packaging

15 01 10 *	packaging containing residues of or contaminated by dangerous substances
------------	--

*: Evidence for disposal must be provided.

Remark:

Must be taken to an underground storage in compliance with the German Recycling Act (Kreislaufwirtschaftsgesetz; KrWG), if necessary after pre-treatment. Do not allow to enter into surface water or drains.

Waste treatment options





Appropriate disposal / Product:

Consult the appropriate local waste disposal expert about waste disposal.

13.2. Additional information

Recommended cleaning agent: acetone, ethyl acetate

SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.1. UN number or ID number			
UN 1866	UN 1866	UN 1866	UN 1866
14.2. UN proper shipping name			
HARZLÖSUNG	HARZLÖSUNG	RESIN SOLUTION	RESIN SOLUTION
14.3. Transport hazard class(es)			
 3	 3	 3	 3
14.4. Packing group			
II	II	II	II
14.5. Environmental hazards			
No	No	No	No
14.6. Special precautions for user			
Special Provisions: 640D Limited quantity (LQ): 5 L Excepted Quantities (EQ): E2 Hazard identification number (Kemler No.): 33 Classification code: F1 Tunnel restriction code: (D/E)	Special Provisions: 640D Limited quantity (LQ): 5 L Excepted Quantities (EQ): E2 Classification code: F1	Special Provisions: - Limited quantity (LQ): 5 L Excepted Quantities (EQ): E2 EmS-No.: F-E, S-E Remark: Special Case: S-E: No thorough cleaning of spillage site necessary. Residues will dry out and coat surfaces. Stowage Category B	Special Provisions: A3 Limited quantity (LQ): Y341 Excepted Quantities (EQ): E2

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Oct 2025

Print date: 13 Oct 2025

Version: 2.2

OBTEGO
innovative surface protection

Page 9/10

OBTEGO X-100 (A) Harz (Primer)

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
--------------------------	-----------------------------	----------------------	------------------------------------

14.7. Maritime transport in bulk according to IMO instruments

No data available

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Other regulations (EU):

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances [Seveso-III-Directive], Hazard categories:

- P5c Flammable liquids of Categories 2 or 3, not covered by P5a and P5b

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients are included.

Seveso category P5c FLAMMABLE LIQUIDS

Quantity threshold (in tonnes) for use in lower-tier establishments 5,000 t

Quantity threshold (in tonnes) for use in upper-tier establishments 50,000 t

Regulation(EC) No 1907/2006 ANNEX XVII Restriction conditions: 3.

Directive 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients are included.

Regulation (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVE OUTPUTS (Upper concentration limit for authorisation under Article 5(3))

None of the ingredients are present.

Annex II - DECLARABLE EXPLOSIVE EXIT SUBSTANCES

None of the ingredients is included.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients are included.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug substitutes

None of the ingredients are included.

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds:

Volatile organic compounds (VOC) content in percent by weight: 0 weight-%

15.1.2. National regulations

[DE] National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Störfallverordnung (12. BImSchV)

for substances contained in the product:

Hazard categories:

- P5c Flammable liquids of Categories 2 or 3, not covered by P5a and P5b

Technische Anleitung zur Reinhaltung der Luft (TA-Luft)

Remark:

Technische Anleitung zur Reinhaltung der Luft (TA-Luft) Class(es)II Weight fraction: 50 -100%

Water hazard class

WGK:

1 - slightly hazardous to water

15.2. Chemical Safety Assessment

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 10 Oct 2025

Print date: 13 Oct 2025

Version: 2.2

OBTEGO
innovative surface protection

Page 10/10

OBTEGO X-100 (A) Harz (Primer)

SECTION 16: Other information

16.1. Indication of changes

No data available

16.2. Abbreviations and acronyms

See overview table at www.euphrac.eu

16.3. Key literature references and sources for data

Substance name	Type	source of supply
2-(N-methyl-p-toluidino)ethanol CAS No.: 2842-44-6 EC No.: 220-638-5	Classification of the substance or mixture; LD ₅₀ oral; LC ₅₀ ; NOEC; LOEC	Source: European Chemicals Agency, http://echa.europa.eu/

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
flammable liquids (<i>Flam. Liq. 2</i>)	H225: Highly flammable liquid and vapour.	
Skin corrosion/irritation (<i>Skin Irrit. 2</i>)	H315: Causes skin irritation.	
Respiratory or skin sensitisation (<i>Skin Sens. 1</i>)	H317: May cause an allergic skin reaction.	
STOT-single exposure (<i>STOT SE 3</i>)	H335: May cause respiratory irritation.	

16.5. List of relevant hazard statements and/or precautionary statements from sections 2 to 15

Hazard statements	
H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H411	Toxic to aquatic life with long lasting effects.

16.6. Training advice

No data available

16.7. Additional information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.